



TECHNICAL INFORMATION / TEKNISK INFORMATION












Type A =
smooth surface




Type B =
surface with "knobs"

BERGO EXCELLENCE EXTREME

Material:			Environmentally friendly recyclable UV-stabilized composite.	/ Miljövänlig återvinningsbar UV-stabiliserad komposit.
Size of tile: /Plattans storlek:		EN427	A and B: 302,1 x 302,1 mm. 1 m ² / box = 11 tiles. 5 m ² / box = 55 tiles. 1,09 m ² /sheet = 4x3 tiles.	
Thickness of tile: /Plattans tjocklek:		EN428	A: 14 mm. B: 14,5 mm.	
Weight: /Vikt:		EN430	A: 1 tile: 0,43 kg. 5 m ² : 24,20 kg. 4x3 tiles: 5,16 kg.	B: 1 tile: 0,47 kg. 5 m ² : 26,40 kg (Maxi-pack) 4x3 tiles: 5,64 kg (Preassembled sheets).
Point load: /Punktbelastning:		QUALIFIED TEST BY BERGO	1000 ton / 1 m ² = 10 000 kg/dm ²	
Light fastness: /Ljusbeständighet:		EN 14836 (>3) ISO 105-B02 (1-8)	4-5 7-8	
Weather Fastness /UV- Florida test (1-5):		ASTM D1435 ASTM G154 Cycle A	4/5	
Slip resistance: /Halkmotstånd:		SSEN-13893	>0,4	
Impact resistance: /Slagtåligghet:		ISO179/2-1eU	+23 °C = >100 kJ/m ² / -30 °C = >100 kJ/m ²	
Fire category /Brandklassning:		IMO MSC/Circ. 1120, 2000 HSC Code 7 and IMO FTP Code	Certificate No. MED-B-9103	Certificate No. MED-D-1940

Packaging:	Quantity / packaging unit:	Quantity / pallet:	Size of pallet:
Maxi-pack carton	5 m ² = 55 tiles	1 pallet = 36 cartons = 180 m ²	1,30 x 0,98 x 2,60 m = 3,3 m ³ , 970 kg gross weight
Preassembled sections	1 section = 4 x 3 tiles = 1,1 m ²	1 pallet = 75 sections = 81,8 m ²	1,26 x 0,96 x 1,23 m = 1,49 m ³ , 448 kg gross weight



Med B, D
DNN



By normal use and treatment
the material guarantee time
is 10 years.



Bergo Flooring AB fulfills the
requirements of ISO 9001.



SYSTEM
1

www.bergoflooring.com

